

3COM® ADSL WIRELESS 11N FIREWALL ROUTER

802.11n technology enables faster information transfer, wirelessly, over longer ranges



3Com ADSL Wireless 11n Firewall Router

OVERVIEW

The 3Com® ADSL Wireless 11n Firewall Router delivers significant wireless speed and range improvements over IEEE 802.11g. Its robust and high-speed routing engine, security features and integrated ADSL2/2+ modem allow up to 253 wired and wireless users to share a single ADSL connection.

With wireless speeds of up to 300 Mbps, this router—compliant with the IEEE 802.11n draft 2.0 standard and Wi-Fi CERTIFIED™—is able to handle high-bandwidth applications confidently. IP and ATM Quality of Service (QoS) helps ensure that critical time-sensitive traffic gets the priority needed for quality communications.

Advanced security features, including 128-bit WPA™/WPA2™ wireless encryption, firewall, hacker pattern detection, VPN IPSec, URL filtering, and IP and MAC address filtering, provide high level protection against hacking and snooping. Easy to set up and use, this product is backed by a two-year hardware warranty.

KEY BENEFITS

HIGH-SPEED SHARED WIRED AND WIRELESS CONNECTIVITY

Delivering wireless speeds of up to 300 Mbps, the 3Com ADSL Wireless 11n Firewall Router easily handles large data transfers and Internet downloads, including those from multimedia applications.

This router is backward-compatible with IEEE 802.11b and .11g wireless devices, preserving existing network investments. It is Wi-Fi CERTIFIED and interoperates with other certified Wi-Fi® products.

The 3Com ADSL Wireless 11n Firewall Router has a built-in four-port 10/100 Ethernet LAN switch, which enables up to 253 total (32 wireless) users to securely share a single ADSL Internet connection, reducing broadband expenses, and the integrated ADSL2/2+ modem eliminates the need for a separate modem.

STANDARDS-BASED FOR INTEROPERABILITY

The 3Com ADSL Wireless 11n Firewall Router uses IEEE 802.11n draft 2.0 technology to deliver significant wireless speed and range improvements over IEEE 802.11g networks. With two external and one internal antennas and advanced Multiple Input Multiple Output (MIMO) technology, the enhanced wireless range of this router helps provides single point coverage in small office and home networking environments, and can eliminate dead spots common with other wireless LANs.

HIGHLY-EVOLVED SECURITY FEATURES

Advanced wireless security and multiple firewall features offer high levels of protection for the network. To help shield wireless connections, this router provides 128-bit WPA/WPA2 with TKIP/AES encryption that encodes and protects information, providing maximum security. For legacy clients, WEP encryption is also supported.



3COM

KEY BENEFITS (CONTINUED)

URL filtering, a Stateful Packet Inspection (SPI) firewall with hacker pattern detection and other security features help protect the entire network from attacks and other Internet security risks. Support for initiation and termination of Internet Protocol security (IPSec) tunnels helps enable security between business sites.

ADVANCED QUALITY OF SERVICE (QOS) FOR QUALITY-SENSITIVE INFORMATION TRANSFER

A unique combination of features helps assure reliable delivery—with no interruption—of delay-sensitive information like voice and video.

RELIABLE, SIMPLE TO USE AND GREEN

Designed to meet 3Com's proven standards of quality, reliability is assured and supported by a two-year hardware warranty. A browser-based user interface and simple setup wizards ease installation, configuration and administration.

All-in-one design integrates five functions—ADSL2/2+ modem, .11n access point, 4-port switch, firewall and routing—into one product, simplifying deployment.

With the push of a button, Wi-Fi Protected Setup™ (WPS) is easily enabled, automating and simplifying the creation of a secure wireless network. Other features like a Wi-Fi “on-off” button make this product easy-to-use while also reducing power costs.

SEAMLESS INTEROPERABILITY FOR .11N

3Com offers a variety of compatible 802.11n wireless devices:

- > 3Com Wireless 11n PCI Adapter, 3CRPCIN175
- > 3Com Wireless 11n USB Adapter, 3CRUSBN175

FEATURES AND BENEFITS

SHARED INTERNET ACCESS

Wired and wireless user support	Enables up to 253 total (32 wireless) users to share a single ADSL connection, making the most of your broadband service
All-in-one device	Combines ADSL 2/2+ modem, 802.11n access point, router, firewall and 4-port switch in one box to allow easy and secure broadband access

HIGH-SPEED WIRELESS CONNECTIVITY

802.11n 300 Mbps performance	Delivers connections significantly faster than 802.11g
Backward compatible with 11b/g users	Supports high speeds while protecting existing investments
Multiple Input Multiple Output (MIMO)	Advanced MIMO technology provides enhanced wireless range and coverage area for improved roaming and ubiquity
Packet bursting	Increases throughput by sending more frames in a given time period

ROBUST SECURITY

WPA/WPA2 (Wi-Fi Protected Access) and WEP (Wired Equivalent Privacy)	Supports advanced 128-bit WPA/WPA2 encryption, and 40-/64- and 128-bit WEP encryption for legacy wireless clients
Multi-level wireless security	Provides additional wireless security with SSID Broadcast Disable and MAC filtering
Firewall	Full SPI firewall, access control rules, DoS protection and other features helps protect your network from the security risks of always-on broadband connections
Internet protocol security (IPSec)	Enables secure site-to-site communication with up to five concurrent IPSec tunnels
Proxy Address Resolution Protocol (ARP)	Proxy ARP allows secure setup of public servers behind router firewall

NETWORKING AND QOS

IP (RIP 1 and 2) and static routing	Allows the router to be used in multi-network environments
WiFi Multimedia (WMM®), QoS and VLAN support	Improves the user experience for audio, video and voice applications
Internet Group Management Protocol (IGMP) snooping and query	Allows more efficient use of resources when supporting multicast-based applications like online streaming video and gaming
Wi-Fi Distribution System (WDS)	Easily expands network coverage using compatible WDS-enabled APs
Dynamic Domain Name Service (DNS)	Enables Internet connections with dynamic IP addresses to network applications such as Web or FTP servers that normally require static IP addresses (requires subscription with Dynamic DNS providers)

BUILT-IN EASE OF USE

Set-up wizards, pre-set defaults, and intuitive browser interface	Makes set up and configuration easy
Easy one-button access to WPS and wireless connectivity enablement	Secure your wireless network with just one push of a button; reduce power consumption by turning off wireless connectivity when not needed

WIRELESS PERFORMANCE COMPARISON

	IEEE SPECIFICATION		
PERFORMANCE MEASURE[‡]	802.11b	802.11g	802.11n [¥]
MAXIMUM DATA RATE	11 Mbps	54 Mbps	300 Mbps
MAXIMUM OPERATING RANGE	35 m (115 ft)	35 m (115 ft)	70 m (230 ft)

[‡] Performance measures are theoretical maximums based on the IEEE specification. Actual performance may vary, based on total number of simultaneous users, amount of traffic generated by each user, physical and environmental conditions and other electronic devices in the area.

[¥] Draft 2.0 standard. Performance is with 2 streams and when using MIMO.

SPECIFICATIONS

MINIMUM SYSTEM REQUIREMENTS

Operating system that supports an Ethernet connection with an IP stack
 Computer with an Ethernet 10BASE-T or 10/100 interface configured for network communication
 Wi-Fi-certified IEEE 802.11n draft 2.0-compliant, 802.11g or 802.11b adapter cards for wireless access
 An active ADSL broadband connection
 Installation CD requires Windows 95 or later

USERS SUPPORTED*

Up to 253 total simultaneous users
 32 wireless users; MAC filter 32 clients

HARDWARE CONFIGURATION

LAN: 4 autosensing 10BASE-T/ 100BASE-TX ports
 WAN: 1 RJ-11 (3CRWDR300A-73) or 1 RJ-45 (3CRWDR300B-73)
 Wi-Fi on/off button
 Wi-Fi protected setup (WPS) button
 3 antennas: 2 fixed external and 1 internal

WIRELESS NETWORKING

Wireless distribution system (WDS); repeater mode for up to 4 links
 WDS over WEP and WPA/WPA2
 20 Mhz and 40 Mhz channels support
 WMM (IEEE 802.11e)
 WiFi protected setup (WPS); PIN and PBC modes
 SSID broadcast disable
 MAC address filtering
 300 Mbps[†] performance

FREQUENCY BAND

2.4-2.4835 GHz

WIRELESS MEDIUM

OFDM, CCK

MEDIA ACCESS PROTOCOL

CSMA/CA

PROTOCOL SET

Dynamic and static IP addressing
 MAC address cloning
 DHCP server
 IP to MAC address binding
 NAT/PAT (with TCP and UDP), PPPoE, PPTP, IP, PAP, CHAP, MS CHAP, IPCP, SNTP, L2TP

ROUTING AND NETWORKING

RIP 1 and 2
 Static routing
 IGMP snooping
 Port-based VLANs

ADSL STANDARDS

ANSI T1.413 issue 2
 ITU G.992.1 (G.DMT)
 ITU G.992.2 (G.lite)
 ITU G.992.3 (ADSL2 DMT)
 ITU G.992.4 (ADSL2 G.lite)
 ITU G.992.5 (ADSL2+)

ATM SUPPORT

Traffic shaping (UBR/CBR)
 OAM (I.610) F4/F5 support
 PPP over Ethernet (RFC 2516)
 PPP over ATM
 Support for up to 8 PVCs

QUALITY OF SERVICE

WMM
 Differentiated services (DiffServ); mark/remark up to 16 mapping rules

SECURITY

128-bit WPA/WPA2 with TKIP/AES wireless encryption
 40-/64-bit and 128-bit WEP encryption
 URL and keyword filtering (black and white lists, 20 entries)
 Special application support (port triggering; 20 entries accepting commas and hyphens)
 Virtual server support (port forwarding; 20 entries)
 Time scheduling (10 rules)
 PC privileges (IP address-based ACL; 10 groups)
 Proxy ARP support (RFC 1027)
 Virtual DMZ support (up to 8 servers)
 SSID Broadcast Disable
 MAC address filtering
 NAT/PAT/NAT off
 Traffic metering
 Full stateful packet inspection (SPI) firewall with DoS/DDoS protection
 NAT-T draft 2.0
 SIP ALG

VPN

IPSec, PPTP and L2TP/IPSec passthrough
 Initiation/termination of up to five concurrent IPSec tunnels
 Encryption: DES, 3DES, AES-128, AES-256
 Key management: IKE (main and aggressive modes)
 IKE keep-alive
 FQDN support
 PFS

* Total number of simultaneous users depends on speed of broadband connection and amount of traffic generated by each user.

[†] Wireless performance depends on number of users, physical and environmental conditions and other electronic devices in the area.

SPECIFICATIONS (CONTINUED)

CONFIGURATION AND MANAGEMENT

Browser-based administration
 Preset defaults
 Remote management via HTTP
 Save and restore configuration files
 E-mail alerts
 Syslog server support
 SNMP v1/2c (MIBII)
 LED indicators
 Power (3Com logo, white)
 Alert (amber)
 DSL sync (blue)
 Data DSL (blue)
 Wireless LAN (blue)
 LAN ports 1-4 (blue)
 WPS (blue)

DIMENSIONS

Height (with rubber feet):
 4.0 cm (1.6 in), antenna folded; 10.0 cm (3.9 in), antenna unfolded
 Width: 17.8 cm (7.0 in)
 Depth (with antenna): 16.0 cm (6.3 in)
 Weight: 300g (0.66 lb)

POWER

Operating output: 15 VDC, 1A
 Maximum power consumption: 12W
 Supplied via included energy efficient power supply

REGULATORY/AGENCY APPROVALS

Safety: UL 60950-1, CSA 22.2 No. 60950-1-03, EN 60950-1: 2001, IEC 60950-1: 2001.
 Emission: CFR Title 47, FCC Part 15 Subpart B & C, ICES-003, Industry Canada RSS-210, Industry Canada RSS-Gen, EN 300 328, EN 301 489-1/17, EN 55022 Class B, EN 55024
 Environmental: EN 60068 (IEC 68)
 Telecom: FCC Part 68, IC CS-03

PACKAGE CONTENTS

3Com ADSL Wireless 11n Firewall Router
 Power supply
 Install Guide
 CD ROM containing Discovery program and User Guide
 Four rubber feet
 One straight-through category 5 UTP RJ-45 patch cable for connection to PC
 One cable for connection to ADSL line (RJ-11 for 3CRWDR300A-73 or RJ-45 for 3CRWDR300B-73)

WARRANTY AND OTHER SERVICES

Two Year Limited Hardware Warranty
 Limited Software Warranty for 90 days
 30 days of telephone technical support
 Refer to www.3com.com/warranty for details.



ORDERING INFORMATION

PRODUCT DESCRIPTION	MODEL	3COM SKU
3Com ADSL Wireless 11n Firewall Router (ITU Annex A, ADSL over POTS)	WL-603	3CRWDR300A-73
3Com ADSL Wireless 11n Firewall Router (ITU Annex B, ADSL over ISDN)	WL-603	3CRWDR300B-73

Visit www.3com.com for more information about 3Com solutions.

3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064
 3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2009 3Com Corporation. All rights reserved. 3Com and the 3Com logo are registered trademarks of 3Com Corporation in various countries worldwide. Wi-Fi, Wi-Fi Alliance, the Wi-Fi CERTIFIED logo, and WMM are registered trademarks, and Wi-Fi CERTIFIED, WPA, WPA2, and Wi-Fi Protected Setup are trademarks, of the Wi-Fi Alliance. All other company and product names may be trademarks of their respective companies.

While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice.

401089-002 02/09

